

**O. O. MISHCHENKO, V. Y. VOLOVSHCHYKOV, V. F. SHAPO, M. A. GRINCHENKO**

## SYNTHESIS OF LOCAL AREA NETWORK STRUCTURE IN UNCERTAIN CONDITIONS OF INITIAL INFORMATION

The problem of taking into account the uncertainty of the initial information is identified in the tasks of the structure synthesis of local area networks. The analysis of the factors generating uncertainty is carried out, the sources of uncertainty are singled out and the approaches to formalization and research of uncertainty are systematized. Probabilistic-statistical, interval, fuzzy and deterministic approaches were reviewed, as well as statistical, subjective, logical interpretations of probability and stochastic description, concept of interval-probabilistic approach, continuously determined and discretely determined models. The formulation of the problem was formed and it was proposed to apply the theory of fuzzy sets to formalize and study an uncertainty in synthesizing the structure of the local computing network, the main elements of which are user points, the centers of processing of the information, switching devices and communication channels. The implementation of information and computing works which sources are subscriber points, is assigned to the centers of information processing. It is assumed the popularity of volumes of information and computing works and geographical coordinates of the location of network elements. A model for a research problem based on a cost criterion has been developed. Cost parameters are divided into well-defined and having an uncertain nature. Fuzzy parameters are proposed to describe the membership functions of the form "approximately equal" or "is approximately in the interval". Restrictions on technical capabilities of information processing centers, switching devices, traffic in communication channels are singled out. The technology of model research based on the idea of solving the problems of linear programming in fuzzy statement is proposed. The technology provides the decision maker with information about the network structure, its cost and the level of ownership of the solution. The results of the work can be used in the analysis of approaches to solving problems of structural-topological synthesis of local area networks, design, development and implementation of appropriate software solutions.

**Keywords:** local area network, uncertainty, probabilistic and statistical approaches, interval approach, fuzzy approach, deterministic approaches, structure synthesis, model, fuzzy cost criteria, research technology

## **О. О. МІЩЕНКО, В. Ю. ВОЛОВЩИКОВ, В. Ф. ШАПО, М. А. ГРИНЧЕНКО**

### СИНТЕЗ СТРУКТУРИ ЛОКАЛЬНОЇ ОБЧИСЛЮВАЛЬНОЇ МЕРЕЖІ В УМОВАХ НЕВИЗНАЧЕНОСТІ ВИХІДНОЇ ІНФОРМАЦІЇ

Ідентифікована проблема врахування невизначеності вихідної інформації в задачах синтезу структури локальних обчислювальних мереж. Проведено аналіз факторів, що породжують невизначеність, виділені джерела невизначеності і систематизовані підходи до формалізації і дослідження невизначеності. Розглянуті ймовірно-статистичний, інтервальний, нечіткий і детермінований підходи, а також статистична, суб'єктивна, логічна інтерпретація ймовірності і стохастичний опис, концепція інтервально-ймовірного підходу, модель безперервно-детермінована і дискретно-детермінована. Сформульовано постановку задачі і запропоновано застосовувати теорію нечітких множин до формалізації і дослідження невизначеності при синтезі структури локальної обчислювальної мережі, основними елементами якої є абонентські пункти, центри обробки інформації, комутаційні прилади та канали зв'язку. Виконання інформаційно-обчислювальних робіт, джерелами яких є абонентські пункти, покладено на центри обробки інформації. Припускається, що обсяги інформаційно-обчислювальних робіт і географічні координати розташування елементів мережі є відомими. Розроблено модель задачі дослідження на основі критерію вартості. Параметри вартості розділені на чітко задані і ті, що мають невизначену природу. Нечіткі параметри запропоновано описувати функціями належності виду "приблизно дорівнює" або "знаходитьться приблизно в інтервалі". Виділено обмеження на технічні можливості центрів обробки інформації, комутаційних приладів, трафік в каналах зв'язку. Запропоновано технологію дослідження моделі, яка заснована на ідеї вирішення задач лінійного програмування в нечіткій постановці. Технологія забезпечує особу, яка приймає рішення, інформацією про структуру мережі, її вартість та рівень приналежності рішення. Результати роботи можуть бути використані при аналізі підходів до вирішення задач структурно-топологічного синтезу локальних обчислювальних мереж, проектуванні, розробці та впровадженні відповідних програмних рішень.

**Ключові слова:** локальна обчислювальна мережа, невизначеність, ймовірно-статистичні підходи, інтервальний підхід, нечіткий підхід, детерміновані підходи, синтез структури, модель, нечіткий критерій вартості, технологія дослідження

## **А. А. МИЩЕНКО, В. Ю. ВОЛОВЩИКОВ, В. Ф. ШАПО, М. А. ГРИНЧЕНКО**

### СИНТЕЗ СТРУКТУРЫ ЛОКАЛЬНОЙ ВЫЧИСЛИТЕЛЬНОЙ СЕТИ В УСЛОВИЯХ НЕОПРЕДЕЛЕННОСТИ ИСХОДНОЙ ИНФОРМАЦИИ

Идентифицирована проблема учета неопределенности исходной информации в задачах синтеза структуры локальных вычислительных сетей. Проведен анализ факторов, порождающих неопределенность, выделены источники неопределенности и подходы к формализации и исследованию неопределенности. Рассмотрены вероятностно-статистический, интервальный, нечеткий и детерминированный подходы, а также статистическая, субъективная, логическая интерпретация вероятности и стохастическое описание, концепция интервально-вероятностного подхода, модель непрерывно-детерминированная и дискретно-детерминированная. Сформулирована постановка задачи и предложено применять теорию нечетких множеств к формализации и исследованию неопределенности при синтезе структуры локальной вычислительной сети, основными элементами которой являются абонентские пункты, центры обработки информации, коммутационные приборы и каналы связи. Выполнение информационно-вычислительных работ, источниками которых являются абонентские пункты, возложено на центры обработки информации. Предполагается, что объемы информационно-вычислительных работ и географические координаты расположения элементов сети известны. Разработана модель задачи исследования на основе критерия стоимости. Параметры стоимости разделены на четко заданные и имеющие неопределенную природу. Нечеткие параметры предложено описывать функциями принадлежности вида "приблизительно равно" или "находится приблизительно в интервале". Выделены ограничения на технические возможности центров обработки информации, коммутационных приборов, трафик в каналах связи. Предложена технология исследования модели, основанная на идеи решения задач линейного программирования в нечеткой постановке. Технология обеспечивает лица, принимающего решения, информацией о структуре сети, ее стоимости и уровне принадлежности решения. Результаты работы могут быть использованы при анализе подходов к решению задач структурно-топологического синтеза локальных вычислительных сетей, проектировании, разработке и внедрении соответствующих программных решений.

**Ключевые слова:** локальная вычислительная сеть, неопределенность, вероятностно-статистические подходы, интервальный подход, нечеткий подход, детерминированные подходы, синтез структуры, модель, нечеткий критерий стоимости, технология исследования

**Introduction.** The efficiency of using computing and peripheral equipment is increased due to the implementation of local area networks (LAN) [1].

It is necessary to go through many stages to get benefits from using the LAN: determine the purpose, choose the implementation option, analyze information flows, identify data storage and processing centers, form the structure, configure and test the LAN. One of the key stages is the LAN structure formation. It is important to take into account many different parameters, including those that may have an indefinite nature. Therefore, issues of formalization and uncertainty research are important and relevant.

**Analysis of approaches to the formulation and study of uncertainty.** We can identify factors causing uncertainty [2]: complexity, human and environmental factors. Then the sources of uncertainty can be divided into three groups: the randomness of the processes under consideration, the distortion and inaccessibility of information about possible events and processes, and opposition from other systems.

Systematizing [3–7], we single out approaches to formalization and the study of uncertainty.

Probabilistic-statistical approaches. This class of approaches is based on a statistical, subjective, and logical interpretation of probability with a stochastic description. The statistical interpretation of probability identifies probability with the relative frequency of a mass random event occurrence at sufficiently long tests. In conditions of limited experiment we are limited to selective estimates. The reliability of the results obtained on their basis depends on the existence of qualitative and voluminous statistical information. In a subjective interpretation of the probability, the probability is interpreted as the "degree of confidence" in the value of the uncertainty factor under consideration. The logical interpretation of probability is associated with an attempt to validate hypotheses based on logical considerations. Stochastic description is expedient if uncertainty factors can be attributed to probabilistic character and their probability density can be set.

The interval approach assumes the description of uncertainty factors in the interval form by the range of possible values of variables or dependencies. Accordingly, the length of the range is interpreted as a natural measure of uncertainty. The concept of the interval-probabilistic approach describes the available data by a set of close probability distributions, and weakens the assumption of statistical homogeneity of the observed events in the construction of probability hypotheses.

The fuzzy approach assumes that the elements of human thinking are not numbers, but sets, for which the transition from "belonging" to "non-belonging" is continuous. The main features of the approach are: the use of fuzzy and linguistic variables, the use of simple and complex relationships.

Deterministic approaches to accounting for uncertain factors play a significant role in the practice of creating various systems. Input and output variables are deterministic, internal connections in the system are known. It is assumed that there is a causal relationship between the

choice of a certain alternative and the onset of a corresponding outcome. Continuously deterministic and discretely deterministic models can be used to model systems.

**Formulation of the problem.** When building the structure of a LAN, it is important to take into account its constituent elements, the links between them, the presence of information flows, and the impact of external and internal environmental factors. This leads to the fact that the synthesis of the LAN structure can be influenced by uncertainty. Ignoring the accounting for uncertainty may lead to inadequate models and the adoption of unjustified decisions. Probabilistic-statistical, deterministic interval and fuzzy approaches can be used to formalize and assess uncertainties. If there is a lack of information for the application of probabilistic models, difficulties in operation with random variables, the ability to work with interval values within the limits of the fuzzy approach, it is expedient to apply the theory of fuzzy sets.

Thus, the paper proposes to consider the problem of the synthesis of the LAN structure in the conditions of uncertainty of the initial information, the generating factor of which we will consider the external environment. A fuzzy approach is applied to formalize uncertainty.

When building a LAN structure, problem statements based on the following criteria may be relevant depending on the performance indicator: cost, performance, reliability [8, 9]. Since the external environment has the greatest influence on the parameters that are independent of the internal processes of the enterprise, attention is paid to the cost criterion.

Among the variety of topological realizations of LAN [10], the paper considers radial node with an arbitrary number of levels of data switching.

Based on the ideology of the implementation and use of LAN, we will assume that the LAN has the task of serving the set  $I$  ( $i \in I$ ) subscriber stations (SS). SS are the sources of informational computational works (ICW), the execution of which is entrusted to the set  $J$  ( $j \in J$ ) of information processing centers (PIC). The transfer of the ICW from the SS to the PIC is performed via communication channels (CC) using the set  $K$  ( $k \in K$ ) of switching devices (SD). It is assumed that the ICW volumes  $\{h_{ij}\}$ , the geographical coordinates of the SS, PIC and SD are known, and the distance vector  $d = \{d_{vw}\}$ , where  $v, w \in I \cup J \cup K$ ,  $v \neq w$  is defined accordingly.

Thus, the aim of the work is to develop a model for the synthesis of the LAN structure based on the cost criterion, taking into account the uncertainty of the initial data. The development of technology for the study of the synthesis model of the LAN structure is also given special attention in the work.

**Model of synthesis of LAN structure.** From the point of view of the presence in the LAN structure of the SS, PIC, SD, each of which can be implemented by one of the valid options  $s \in S_i$ ,  $q \in Q_j$ ,  $m \in M_k$ , we introduce the vector of Boolean variables  $x = \{x_{is}\}$ ,  $y = \{y_{jq}\}$ ,  $z = \{z_{km}\}$ , and the topology and variants of the implementation of the CC with the type  $l$  from the admissible set  $L$  will be described with  $\alpha = \{\alpha_{ki}^l\}$ ,  $\beta = \{\beta_{kj}^l\}$ ,  $\gamma = \{\gamma_{jk}^l\}$  and  $\varepsilon = \{\varepsilon_{kn}^l\}$ . Moreover, let  $\alpha_{ki}^l$  be a Boolean variable, which

determines the variant of connecting the SS  $i$  to the output of the SD  $k$  using CC  $l$ ,  $\beta_{kj}^l$  – PIC  $j$  to the output of the SD  $k$  using CC  $l$ ,  $\gamma_{jk}^l$  – PIC  $j$  to the output of the SD  $k$  using CC  $l$ , and  $\varepsilon_{kn}^l$  – from SD  $n$  to SD  $k$  using CC  $l$ . To build a LAN cost function, we define the vector of parameters  $a = \{a_{is}\}$ ,  $c = \{c_{jq}\}$ ,  $r = \{r_{km}\}$  and  $w = \{w_l\}$ , which we associate with the costs of using SS, PIC, SD and CC models with various technical characteristics.

Analysis [11] showed the expediency of separating all cost parameters into two subsets. Let the first subset form a set of parameters that can be clearly specified  $\bar{a} = \{\bar{a}_{is}\}$ ,  $\bar{c} = \{\bar{c}_{jq}\}$ ,  $\bar{r} = \{\bar{r}_{km}\}$  and  $\bar{w} = \{\bar{w}_l\}$ .

We associate the second subset with a set of parameters, the formation of which can be influenced by the external environment and which can have an indefinite nature  $\tilde{a} = \{\tilde{a}_{is}\}$ ,  $\tilde{c} = \{\tilde{c}_{jq}\}$ ,  $\tilde{r} = \{\tilde{r}_{km}\}$  and  $\tilde{w} = \{\tilde{w}_l\}$ . To describe the latter, we will use the elements of the fuzzy sets theory and put in conformity with each fuzzy parameter the accessory function (AF) of the form "approximately equal to" or "is approximately in the range"  $\mu(\tilde{a}_{is})$ ,  $\mu(\tilde{c}_{jq})$ ,  $\mu(\tilde{r}_{km})$  and  $\mu(\tilde{w}_l)$ .

The physical connection of the PIC  $j$  of the variant  $q$  to the SD is possible if the PIC has active  $g_{jq}$  network interfaces. The maximum number of connections to the SD SS, PIC and SD is limited by the permissible number of ports  $\bar{u}_{km}$  of the SD  $k$  with technical characteristics  $m$ . In order to avoid packet loss, the total traffic of the  $f_{tp}$  channel ( $t, p$ ) connected to the SD  $p$  must not exceed the bandwidth  $\bar{u}_{pm}$  of this SD. At the same time, the total traffic of each channel ( $t, p$ ) must not exceed the bandwidth of the CC  $b_{tp}^l$  when it is implemented by type  $l$ .

Therefore, the LAN structure must satisfy the following constraints.

Limitations on the technical capabilities of the PIC for connecting to them the SD:

$$N_j(\{y_{jq}\}, \{g_{jq}\}, \{\gamma_{jk}^l\}) \geq 0, j \in J.$$

Limitations on the technical capabilities of the SD to connect to them the SS, PIC and SD:

$$P_k(\{\alpha_{ki}^l\}, \{\beta_{kj}^l\}, \{\varepsilon_{kn}^l\}, \{\bar{u}_{km}\}) \geq 0, k \in K.$$

Limitations on traffic entering to SD:

$$T_k^1(\{f_{ik}\}, \{z_{km}\}, \{\bar{u}_{km}\}) \geq 0, k \in K.$$

Restrictions on traffic in the CC between the SS and SD, PIC and SD, SD and SD:

$$T_{ki}^\alpha(\{f_{ki}\}, \{\alpha_{ki}^l\}, \{b_{ki}^l\}) > 0, k \in K, i \in I_k;$$

$$T_{kj}^\beta(\{f_{kj}\}, \{\beta_{kj}^l\}, \{b_{kj}^l\}) > 0, k \in K, j \in J_k;$$

$$T_{jk}^\gamma(\{f_{jk}\}, \{\gamma_{jk}^l\}, \{b_{jk}^l\}) > 0, j \in J, k \in K_j;$$

$$T_{kn}^\varepsilon(\{f_{kn}\}, \{\varepsilon_{kn}^l\}, \{b_{kn}^l\}) > 0, k, n \in K.$$

We define the fuzzy criterion of LAN cost, in the form of a function  $F$ , as the algebraic sum of the function  $\bar{F}$  with clearly defined parameters and fuzzy  $\tilde{F}$ :

$$\bar{F}(\bar{a}, x, \bar{c}, y, \bar{r}, z, \bar{w}, \alpha, \beta, \gamma, \varepsilon, d);$$

$$\tilde{F}(\tilde{a}, x, \tilde{c}, y, \tilde{r}, z, \tilde{w}, \alpha, \beta, \gamma, \varepsilon, d).$$

**Model research technology.** The technology will be based on the results of [12]. Then the AF of fuzzy parame-

ters can be represented as exponential functions. For example, for  $\tilde{a}_{is}$  an AF, that provides a value equal to 1 in  $\tilde{a}_{is}^*$ , will take the form  $\mu(\tilde{a}_{is}) = e^{-(\tilde{a}_{is} - \tilde{a}_{is}^*)^2 / 2D_{is}}$ , where  $D_{is}$  is a parameter of the Gaussian fuzzy value  $\tilde{a}_{is}$ . Therefore, the AF  $F$  will have the form:

$$\mu(F) = e^{-(F - m(x, y, z, \alpha, \beta, \gamma, \varepsilon))^2 / 2D(x, y, z, \alpha, \beta, \gamma, \varepsilon)}.$$

If to suppose that it is required to get such alternative, the generalized characteristic of which as a level of belonging of decision must be not worse than the predetermined value  $\theta$ , we equate  $\mu(F)$  to  $\theta$ . Using classical transformations, we get:

$$(F - m(x, y, z, \alpha, \beta, \gamma, \varepsilon))^2 = -2D(x, y, z, \alpha, \beta, \gamma, \varepsilon) \ln \theta.$$

Following the optimistic scenario of the synthesis of the LAN structure, the cost criterion  $F$  can be represented as:

$$m(x, y, z, \alpha, \beta, \gamma, \varepsilon) - (-2D(x, y, z, \alpha, \beta, \gamma, \varepsilon) \ln \theta)^{0.5}.$$

The pessimistic scenario should comply with the cost criterion  $F$ , defined follows:

$$m(x, y, z, \alpha, \beta, \gamma, \varepsilon) + (-2D(x, y, z, \alpha, \beta, \gamma, \varepsilon) \ln \theta)^{0.5}.$$

Then, by optimizing the obtained function  $F$  with the limitations of the model for the synthesis of the LAN structure, we can find an alternative  $(x, y, z, \alpha, \beta, \gamma, \varepsilon)$ , providing the decision maker with information about the network structure, its cost and the level of the decision not worse than  $\theta$ .

**Conclusion.** The paper deals with the problem of formalization and the study of uncertainty. Probabilistic-statistical, interval, fuzzy and deterministic approaches are analyzed. The problem of the synthesis of the LAN structure in the conditions of uncertainty of the initial information is formulated. The model for the synthesis of the LAN structure formalizes the uncertainty using a fuzzy approach. The model research technology illustrates the peculiarities of solving the problem of LAN structure synthesis in fuzzy formulation.

Further studies will focus on the analysis of approaches to solving problems of structural-topological synthesis of LAN and the development of appropriate software solutions.

## References

- Андерсон К., Минаси М. *Локальные сети: Полное руководство*. К.: ВЕК+, СПб.: КОРОНА прнт, 1999. 624 с.
- Смирнова К.А. Понятие неопределенности экономических систем и подходы к ее оценке. *Вестник МГТУ*. Мурманск: МГТУ, 2008. Том 11. № 2. С. 241–246.
- Воловчиков В.Ю. Подходы к решению задач системной оптимизации в условиях неопределенности исходной информации. *Авіаційно-космічна техніка і технологія*. Харків: Нац. Аерокосмічний ун-т "Харк. авіац. ін-т", 2002. Вип.29. С. 199–203.
- Derhami S., Smith A.E. An Integer Programming Approach for Fuzzy Rule-Based Classification Systems. *European Journal of Operational Research*, 2017. Vol. 256, iss. 3. P. 924–934.
- Кабаева Е.В. Применение методов интервального анализа. *Научный альманах*. Тамбов: ООО Консалтинговая компания ЮКОМ, 2015. № 11-3(13). С. 149–151.
- Авраменко В.П., Ткаченко В.Ф., Середа Л.Б. Принятие управленических решений в условиях неопределенности и нечеткости исходной информации. *Радиоелектроника, информатика, управління*. Запорожье: ЗНТУ, 2010. № 2. С. 101–106.
- Симанков В.С., Бучацкая В.В., Теплоухов С.В. Подход к учету неопределенности исходной информации в системных исследованиях. *Вестник Адыгейского государственного университета*. Майкоп: ФГБОУВПО "Адыгейский государственный университет", 2017. № 3(206). С. 100–108.

8. Олифер В., Олифер Н. *Компьютерные сети. Принципы, технологии, протоколы*. СПб.: Питер, 2018. 992 с.
9. Зайченко Е. Ю. *Анализ и синтез структуры глобальных вычислительных сетей*. К.: ЗАО "Укрспецмонтажпроект", 1998. 107 с.
10. Таненбаум Э. *Компьютерные сети*. СПб.: Питер, 2019. 960 с.
11. Годлевский М.Д., Воловщиков В.Ю. Модель статической задачи структурного синтеза корпоративной информационно-вычислительной системы. *Східно-європейський журнал передових технологій*. Харків: ППТЦ, 2006. № 2/2 (20). С. 110–113.
12. Серая О.В., Зарубин В.С., Зинченко И.В., Лолашвили Б.Г. Решение задач линейного программирования в нечеткой постановке. *Вестник Национального технического университета "ХПИ"*. Харьков: НТУ "ХПИ", 2006. № 11. С. 160–167.

**References (transliterated)**

1. Anderson K., Minasi M. *Lokal'nyye seti: Polnoye rukovodstvo* [Local Area Networks: The Complete Guide]. Kiev, VEK+ Publ., St. Petersburg, KORONA print Publ., 1999. 624 p.
2. Smirnova K.A. *Ponyatiye neopredelennosti ekonomiceskikh sistem i podkhody k yeye otsenke* [The concept of uncertainty of economic systems and approaches to its assessment]. *Vestnik MGTU* [Bulletin of MSTU]. Murmansk, MSTU, 2008. Vol. 11, no. 2, pp. 241–246.
3. Volovshchikov V.Y. *Podkhody k resheniyu zadach sistemnoy optimizatsii v usloviyakh neopredelennosti iskhodnoy informatsii* [Approaches to solving problems of system optimization in the conditions of uncertainty of the initial information]. *Aviatsiyno-kosmichna tekhnika i tekhnologiya* [Aerospace engineering and technology]. Kharkiv, National Aerospace University "Kharkiv Aviation Institute" Publ., 2002. Vip. 29, pp. 199–203.
4. Derhami S., Smith A.E. An Integer Programming Approach for Fuzzy Rule-Based Classification Systems. *European Journal of Operational Research*. 2017, vol. 256, iss. 3, pp. 924–934.
5. Kabayeva E.V. *Primeneniye metodov interval'nogo analiza* [Application of interval analysis methods]. *Nauchnyy al'manakh* [Scientific almanac]. Tambov, Consulting company Ucom LLC Publ., 2015. No. 11-3(13), pp. 149–151.
6. Avramenko V.P., Tkachenko V.F., Sereda L.B. *Prinyatiye upravlencheskikh resheniy v usloviyakh neopredelennosti i nechetnosti iskhodnoy informatsii* [Making management decisions in the face of uncertainty and vagueness of the initial information]. *Radiyoelektronika, informatika, upravlinnya* [Radio electronics, informatics, management]. Zaporozhye, ZNTU Publ., 2010. No. 2, pp. 101–106.
7. Simankov V.S., Buchatskaya V.V., Teplovskikh S.V. *Podkhod k uchetu neopredelennosti iskhodnoy informatsii v sistemnykh issledovaniyah* [Approach to taking into account the uncertainty of the initial information in system studies]. *Vestnik Adygeyskogo gosudarstvennogo universiteta* [Bulletin of the Adygea State University]. Maikop, FSBEI of HPE "Adygea State University" Publ., 2017. No. 3 (206), pp. 100–108.
8. Olifer V., Olifer N. *Komp'yuternyye seti. Printsipy, tekhnologii, protokoly* [Computer networks. Principles, technologies, protocols]. St. Petersburg, Peter Publ., 2018. 992 p.
9. Zaychenko Ye. Yu. *Analiz i sintez struktury global'nykh vychislitel'nykh setey* [Analysis and synthesis of the structure of global computer networks]. Kyiv, CJSC "Ukrspetsmontazhproekt" publ., 1998. 107 p.
10. Tanenbaum E. *Komp'yuternyye seti* [Computer networks]. St. Petersburg, Peter Publ., 2019. 960 p.
11. Godlevskiy M.D., Volovshchikov V.Y. *Model' staticheskoy zadachi strukturnogo sinteza korporativnoy informatsionno-vychislitel'noy sistemy* [The model of the static problem of structural synthesis of a corporate information-computing system]. *Skhidno-yeuropeys'kyj zhurnal peredovykh tekhnologiy* [Eastern European Journal of Advanced Technology]. Kharkiv, PPTC Publ., 2006. No. 2/2 (20), pp. 110–113.
12. Seraya O.V., Zarubin V.S., Zinchenko I.V., Lolashvili B.G. *Resheniye zadach lineynogo programmirovaniya v nechetkoy postanovke* [Solving linear programming problems in fuzzy setting]. *Vestnik Natsional'nogo tekhnicheskogo universiteta "KhPI"*, [Bulletin of the National Technical University "KhPI"]. Kharkiv: NTU "KhPI", 2006. No. 11, pp. 160–167.

Received 03.04.2019

**Відомості про авторів / Сведения об авторах / About the Authors**

**Міщенко Орина Олексіївна** – Національний технічний університет «Харківський політехнічний інститут», студентка; м. Харків, Україна; ORCID: <https://orcid.org/0000-0002-6783-673X>; e-mail: arinochka012@gmail.com

**Воловщиков Валерій Юрійович** – кандидат технічних наук, доцент, Національний технічний університет «Харківський політехнічний інститут», доцент кафедри програмної інженерії та інформаційних технологій управління; м. Харків, Україна; ORCID: <https://orcid.org/0000-0003-4454-2314>; e-mail: valera@kpi.kharkov.ua

**Шапо Владлен Феліксович** – кандидат технічних наук, доцент, Національний університет «Одеська морська академія», доцент кафедри теорії автоматичного управління і обчислювальної техніки; м. Одеса, Україна; ORCID: <https://orcid.org/0000-0002-3921-4159>; e-mail: stani@te.net.ua

**Гринченко Марина Анатоліївна** – кандидат технічних наук, доцент, Національний технічний університет «Харківський політехнічний інститут», доцент кафедри стратегічного управління; м. Харків, Україна; ORCID: <https://orcid.org/0000-0002-8383-2675>; e-mail: marinagrunchenko@gmail.com

**Мищенко Арина Алексеевна** – Національний технічний університет «Харківський політехнічний інститут», студентка; м. Харків, Україна; ORCID: <https://orcid.org/0000-0002-6783-673X>; e-mail: arinochka012@gmail.com

**Воловщиков Валерій Юрійович** – кандидат техніческих наук, доцент; Национальный технический университет «Харьковский политехнический институт», доцент кафедры программной инженерии и информационных технологий управления; г. Харьков, Украина; ORCID: <https://orcid.org/0000-0003-4454-2314>; e-mail: valera@kpi.kharkov.ua

**Шапо Владлен Феликсович** – кандидат техніческих наук, доцент, Национальный университет «Одесская морская академия»; доцент кафедры теории автоматического управления и вычислительной техники; г. Одесса, Украина; ORCID: <https://orcid.org/0000-0002-3921-4159>; e-mail: stani@te.net.ua

**Гринченко Марина Анатольевна** – кандидат технических наук, доцент; Национальный технический университет «Харьковский политехнический институт», доцент кафедры стратегического управления; г. Харьков, Украина; ORCID: <https://orcid.org/0000-0002-8383-2675>; e-mail: marinagrunchenko@gmail.com

**Mishchenko Oryna Oleksiivna** – National Technical University "Kharkiv Polytechnic Institute", student; Kharkiv, Ukraine; ORCID: <https://orcid.org/0000-0002-6783-673X>; e-mail: arinochka012@gmail.com

**Volovshchikov Valeriy Yuriyovich** – Candidate of Technical Sciences (PhD), Docent, National Technical University "Kharkiv Polytechnic Institute", Associate Professor of the Department of Software Engineering and Management Information Technologies; Kharkiv, Ukraine; ORCID: <https://orcid.org/0000-0003-4454-2314>; e-mail: valera@kpi.kharkov.ua

**Shapo Vladlen Felixovich** – Candidate of Technical Sciences (PhD), Docent, National University "Odessa Maritime Academy", Associate Professor Associate Professor of the Department of Theory of Automatic Control and Computer Engineering; Odessa, Ukraine; ORCID: <https://orcid.org/0000-0002-3921-4159>; e-mail: stani@te.net.ua

**Grinchenco Marina Anatoliyvna** – Candidate of Technical Sciences (PhD), Docent, National Technical University "Kharkiv Polytechnic Institute", Associate Professor of the Strategic Management Department; Kharkiv, Ukraine; ORCID: <https://orcid.org/0000-0002-8383-2675>; e-mail: marinagrunchenko@gmail.com